



Intelligent Power Strips (Power Distribution Units)

Intelligent power strips provide a modular and flexible solution for the remote monitoring, control and management of today's power needs to mission critical and remote equipment. If zero down time and maximisation of operations is a pre-requisite, the Unite range of intelligent power strips will provide the solutions you need.



Key Features

- **Local (via LCD display) and remote monitoring of true RMS Amps, Voltage, kWhr & kVA**
- **Available in 10, 13, 16, 32 & 63 Amp load ratings**
- **Single & Three phase versions available**
- **Available in a wide range of socket outlets**
Including IEC, C13, C19, 13A UK & Shuko.
- **UK sockets can be angled for optimum cable dressing**
- **Recommended option providing individual socket outlet fusing & power on indicator for enhanced protection**
- **19" horizontal & vertical options**
With top or bottom power feed options
- **Fitted with an external earthing stud**
- **Cabinet neutral**
Fits any type of cabinet or rack.
- **Optional sequential power-up & remote power on/off**
To individual socket outlets.
- **Quick & simple interfacing with:**
Power-Hawk TH, Power-Hawk 2T, Hawk-i² & Enterprise Device Manager for real time SNMP alarm generation, energy management reporting & trend analysis.



Comrac Limited
Company Number: 2587734
Registered Address: Comrac House, Tournament Way,
Ashby de la Zouch, Leicestershire, LE65 2UU, UK
Tel: +44 (0)1530 560880 Fax: +44 (0)1530 560590
Email: sales@comrac.co.uk www.comrac.co.uk www.unitetp.co.uk





Technical Information

Enclosure	1.2mm mild steel with matt black power coating
Max supported length of power strip	48U
Fixing points	6.5mm holes on steel end bracket
Rated Voltage	230V, AC Nominal Single Phase
Rated Current	Up to 63A
Rated Frequency	48 Hz to 62 Hz
Measuring Accuracy	+/-2% to EN61036 & IEC1036
Operating Temperature	-10 °C to +85°C
Local Display	LCD of RMS current, RMS Voltage, kVA & kWhr
Local Display Resolution	1 Volt, 0.01 Amp, 0.1 kVA, 0.1 kWhr
Supported Outlet Sockets include:	C13 – max rating 10A C19 – max rating 16A Shuko – max rating 16A UK 13A – max rating 13A
Fusing / Indicators	Recommended option to fuse socket outlets individually Standard fuse rating is 3.15A anti surge, other fuse ratings available on request Individual socket outlet power on neon indicators
Communication	SNMP monitoring / management Telnet management JAVA monitoring / management applet ("Viewer") WEB monitoring Terminal configuration
Security	Telnet and WEB access password protection
Upgradeability	Firmware upgradeable using serial or TFTP download
Port Communication	RJ45 socket RS232 to Hawk-i ² and Power-Hawk TH for local configuration
Control	Remote switching with max 24 individual switchable outlets Max switchable current 16A per socket outlet
Certificates & Safety Standards	CE approved EN 60950-2000 EN 61010-1



Comrac Limited
Company Number: 2587734
Registered Address: Comrac House, Tournament Way,
Ashby de la Zouch, Leicestershire, LE65 2UU, UK
Tel: +44 (0)1530 560880 Fax: +44 (0)1530 560590
Email: sales@comrac.co.uk www.comrac.co.uk www.unitetp.co.uk

